



## Cannon Nozzle



## Design Features

- Spray Angle : 15°-65°
- Spray Pattern : Hollow cone spray, spray area in a ring.
- Orifice: 0.8mm/1.0mm/1.2mm/1.5mm
- Material : SS
- Features : Injection Angle can be adjusted, through the fan injection distance of 30-100 meters.

## Order Info

<b>A</b>	-	<b>1/4</b>	-	<b>SS</b>	-	<b>1.0K</b>
Nozzle Type		Inlet Conn		Material Code		Orifice

For NPT threaded connections, add the letter "N" before the nozzle connection size.

## Applications

- Air humidifying purification
- Dust control
- Disinfection

## Performance State

At the stated pressure in bar.

Orifice (mm)	Flow Rate Capacity (L/min)								
	2bar	3bar	4bar	5bar	6bar	7bar	10bar	20bar	35bar
0.8	0.22	0.26	0.31	0.34	0.37	0.4	0.48	0.68	0.9
1.0	0.29	0.33	0.37	0.41	0.43	0.47	0.53	0.7	0.95
1.2	0.32	0.39	0.46	0.51	0.56	0.6	0.72	1	1.3
1.5	0.39	0.48	0.55	0.61	0.67	0.72	0.86	1.3	1.7